



# SAFETY DATA SHEET

## SUPERIOR GLAZES – ENCAPSULATED CAPSIUM

### 1. Product Information

<b>Superior Glazes:</b>	SG013, SG017, SG025, SG027, SG029, SG033, SG037, SG041, SG045, SG067, SG069, SG073, SG077, SG079, SG081, SG087.
-------------------------	---

### 2. Hazardous Ingredients

Entity	%	CAS No.	ACGIH TLV	OSHA PEL
Insoluble Cadmium	<26	12656-57-4 58339-34-7	0.01mg/m <sup>3</sup> (as Cd)	0.2mg/m <sup>3</sup> (as Cd)
Selenium Compounds	<26	7782-49-2	0.01mg/m <sup>3</sup>	0.2mg/m <sup>3</sup>
Zirconium Silicate	0-9	10101-52-7	0.5mg/m <sup>3</sup> (as Zr)	0.5mg/m <sup>3</sup> (as Zr)
Clay/Potash	<15	1302-78-9	N/A	N/A
Calcined Alumina	0-2	1344-28-1	10mg/m <sup>3</sup>	5mg/m <sup>3</sup>
Silica	0-6	14808-60-7	0.1mg/m <sup>3</sup>	0.1mg/m <sup>3</sup>
Zinc Oxide	0-10	1314-13-2	2 mg/m <sup>3</sup>	5mg/m <sup>3</sup>

### 3. Physical and Chemical Properties

<b>Appearance</b>	Colour dependant on pigments present
<b>Odour</b>	Negligible
<b>Boiling Point</b>	N/A
<b>Melting Point</b>	>400°C
<b>Vapour Pressure</b>	N/A
<b>Specific Gravity</b>	1.2-1.45 @ 25 °C
<b>Flash Point</b>	N/A
<b>Flammability Limits</b>	No data
<b>Solubility in Water</b>	Negligible
<b>Viscosity</b>	No data
<b>pH</b>	7.0-8.5
<b>Volatile Organic Comp.</b>	7-14%



#### 4. Hazards Identification

<b>Silica</b>	Crystalline Silica may be present. Crystalline Silica may cause irritation to eyes, skin and the respiratory tract. Prolonged or repeated inhalation of silica, in excess of TLV, may lead to delayed lung injury (silicosis). This material is listed as a possible carcinogen.
<b>Cadmium-sulpho-selenide/ Cadmium</b>	<p>Product contain insoluble cadmium pigments.</p> <p>US OSHA has chosen to regulate occupational exposure to all cadmium compounds, including pigments, as a single category. The standard states that substances containing cadmium are a cancer hazard and can cause lung and kidney disease.</p> <p>Cadmium and cadmium compounds are listed in the Annual NTP Report as carcinogenic to animals, but with only limited evidence of carcinogenicity to humans. This information is based on test results for cadmium compounds other than pigment forms.</p> <p>Although certain cadmium compounds are known to cause kidney damage in humans and has been shown to cause lung cancer in laboratory animals, no chronic health effects have been shown to result from exposure to encapsulated cadmium pigments. Encapsulated cadmium pigments have been shown to be significantly less biologically available and less active than other cadmium compounds.</p>
<b>Component Analysis LD50/LC50:</b>	<p>Cadmium Sulphide (12656-57-4 &amp; 58339-34-7)</p> <p>Oral LD50 Rat: 7080 mg/kg Oral LD50 Mouse: 116mg/kg</p> <p>Selenium (7782-49-2)</p> <p>Oral LD50 Rat: 6700 mg/kg</p>
The product has not been tested. The statements on toxicology have been derived from products of a similar structure and composition.	
<b>Carcinogenicity</b>	This product may be carcinogenic to humans.
<b>Component Carcinogenicity</b>	<p><b>Cadmium Sulphide</b> (12656-57-4 &amp; 58339-34-7). German DFG – Category 2 (considered to be carcinogenic for man); listed under cadmium and its compounds.</p> <p><b>Selenium</b> (7782-49-2) IARC – Supplement 7, 1987; Monograph 9, 1975 (Group 3 not classifiable) German DFG – Category 3B (could be carcinogenic for man).</p>
<b>Routes of entry</b>	Ingestion. Absorption through skin negligible. Inhalation only if sprayed.

#### 5. First Aid Measures

<b>Swallowed</b>	Dilute by drinking water
------------------	--------------------------



<b>Eye</b>	Flush eyes with copious quantities of water for at least 15 minutes. If irritation persists, contact a physician.
<b>Skin</b>	Wash skin with soap and water
<b>Inhaled</b>	Remove from exposure. Apply artificial respiration if breathing has stopped and contact physician.

## 6. Fire/Explosion Hazard

<b>Flash Point:</b>	N/A
<b>Flammable Limits:</b>	N/A
<b>Extinguishing Media:</b>	Not combustible
<b>Special Fire Fighting Procedure:</b>	None
<b>Unusual Fire and Explosion Hazards:</b>	None

## 7. Accidental Release Measures

<b>Spillage:</b>	Uncontaminated material may be recovered and re-used. If contaminated, scoop, vacuum or wash into receptacle for disposal.
<b>Waste Disposal:</b>	Follow Federal or State and Local regulations for disposal. Testing of the waste may be required to determine status under hazardous waste regulations.

## 8. Handling and Storage

<b>Engineering Control:</b>	None
<b>Work Practices:</b>	Store away from food. Do not smoke, eat or drink while handling.
<b>Procedure/ Equipment:</b>	None

## 9. Exposure Controls /Personal Protection

Use of the following protective measures are strongly recommended if the glazes are to be applied by spraying.

The work hygiene practices apply regardless of the method of application.

<b>Respiratory Protection:</b>	Use NIOSH approved dust and/or fume respirator as necessary.
<b>Ventilation:</b>	Local exhaust for spraying.
<b>Protective gloves:</b>	None.
<b>Eye Protection:</b>	For spraying.
<b>Other Protection:</b>	Wear appropriate, clean, protective clothing such as, but not limited to overalls, smocks and aprons.

**Work Practices:**

Food, beverages and smoking materials should not be in the work area. Hygiene is very important. Wash thoroughly before eating, drinking and smoking or applying cosmetics.

**10. Stability & Reactivity Data****Incompatibility:**

N/A

**Stability:**

Stable.

**Hazardous decomposition:**

N/A

**Hazardous polymerisation:**

N/A

**Conditions to avoid:**

Fumes from firing, inhalation of spray.

**11. Toxicological Information****Hazard to Humans:**

None during normal use. Harmful if inhaled or swallowed.

**Do not spray apply**

If glaze is spray applied the following warnings apply: Warning: Contains Quartz

1. Possible cancer agent based on tests with laboratory animals.
2. Exposure may cause lung damage.
3. Keep out of reach of children; avoid inhalation.

This product contains chemicals known to cause cancer.

**Health Hazards (acute and chronic):**

Prolonged inhalation of silica, in excess of TLV, over an extended period of time may result in injury to the lungs.

**Additional Information:**

Frits are fused silica glass like substances. The bioavailability may be limited because of the physical nature of the frit. The cadmium pigments used are encapsulated in a zirconium matrix to render the cadmium insoluble. According to current toxicology regulation, these products may be classified as NON-TOXIC.

**12. Ecological Information****Mobility:**

N/A

**Persistence/Degradability:**

N/A

**Bioaccumulation:**

N/A

**Ecotoxicity:**

N/A



### 13. Disposal Considerations

<b>Waste Disposal Method:</b>	Follow Federal, State or Local regulations for disposal. Testing of waste may be required to determine status under hazardous waste regulations.
<b>Waste residue/unused product:</b>	Can be land filled according to local regulations.
<b>Contaminated packaging:</b>	Can be land filled according to local regulations.

### 14. Transport Information

Not regulated. Not dangerous cargo, not restricted by air.
UN Number: N/A

### 15. Regulatory Information

<b>EEC Marketing and labelling hazard symbol:</b>	-	
<b>S Phrases</b>	S20/21	When using do not eat, drink or smoke.
	S22	Do not breathe dust or spray.
	S24/25	Avoid contact with skin or eyes.
	S36/37	Wear suitable protective clothing and gloves.
	S45	In case of accident or if you feel unwell, seek medical advice immediately.

The following components have labelling requirements under Council Directive 67/548/EEC, Annex I.

<b>Cadmium Sulphide (1306-23-6)</b>	Annex #: 048-010-00-4. EINECS #: 215-147-8	
<b>Classification:</b>	Toxic. Carcinogen Category 3.	
<b>Label Information:</b>	R20/22	Harmful by inhalation and if swallowed.
	R40	Possible risk of irreversible effects.
	R48/23/25	Toxic: Danger of serious health damage to health by prolonged exposure through inhalation and if swallowed.
	R53	May cause long-term adverse effects in the



		aquatic environment.
	S1/2	Keep locked up and out of the reach of children.
	S22	Do not breathe dust.
	S36/37	Wear suitable protective clothing and gloves.
	S45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
	S61	Avoid release to the environment. Refer to special instructions / Safety Data Sheets.
Notes:	Concentrations are percentage by weight of metallic element calculated with reference to total weight of the preparation.	
Selenium (7782-49-2)	Annex #: 034-001-00-2. EINECS #: 231-957-4.	
Classification:	Toxic	
Label Information:	R20/22	Harmful by inhalation and if swallowed.
	R33	Danger of cumulative effects.
	R53	May cause long-term adverse effects in the aquatic environment.
	S1/2	Keep locked up and out of the reach of children.
	S20/21	When using do not eat, drink or smoke.
	S28	After contact with skin, was immediately with plenty of water.
	S45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
	S61	Avoid release to the environment. Refer to special instructions / Safety Data Sheets.
WHMIS Status:	Not controlled	



## 16. Other Information

This information is provided without warranty, representation, inducement or license of any kind, except that it is accurate to the best knowledge of Clayman Supplies Limited or obtained from sources believed to be accurate.

Clayman Supplies Limited does not assume any legal responsibility for us or reliance on same. Customers are encouraged to conduct their own tests before using any product. Read the product label.