



SAFETY DATA SHEET

3178 DEEP ORANGE MULTI-COLOUR

1. Identification of substance/preparation and of the company undertaking

Trade Name:	Deep Orange Multi-colour
Chemical Name:	Orange Ceramic Pigment
Synonyms:	None

2. Composition /information on ingredients

Component	CAS	EINECS	% of composition
C.I. Pigment 24	68186-90-3	-	100%

3. Hazards Identification

Inhalation	Excessive exposure may cause symptoms of chronic lung disease.
Ingestion	The product is of low solubility in body fluids and it is likely to be of low toxicity.
Eyes	May cause physical irritation and inflammation.
Skin	The material is not a primary irritant, but as with any abrasive powder it may give rise to minor irritation.

4. First Aid Measures

Inhalation	Remove patient to fresh air, loosen tight clothing and seek medical attention.
Ingestion	Do not induce vomiting, seek medical advice.
Eyes	Wash immediately with copious amounts of water.
Skin	Wash affected area with water.

5. Fire Fighting Hazards

Extinguishing media	Suitable for surrounding fire conditions.
Special Exposure hazard	In the event of fire, the product may emit harmful or toxic fumes.
Personal protective equipment	Self-contained breathing apparatus.



6. Accidental Release Measure

Leaks and spills	Use suitable vacuum equipment where reasonably practicable, otherwise damp down and scoop into a receptacle.
Personal protective equipment	Respiratory protective equipment.

7. Handling & Storage

Handling	Do not eat, drink, or smoke in areas where the material is used. Wash thoroughly after handling the material.
Storage	Store in a dry area.

8. Exposure Control/Personal Protection

Engineering controls	Adequate ventilation should be provided so that Occupational Exposure Limits are not exceeded. Local Exhaust Ventilation is normally recommended.
Personal Protective equipment	Where LEV is not practicable and exposure is likely to be excessive, approved respiratory protection to CEN standards prEN 140, 141, 143 or 149 should be worn. Protective gloves and overalls are recommended for prolonged contact.

9. Physical & Chemical Properties

Appearance and Odour	Orange powder, odourless
Flash Point (°C)	N/A
Flammability	Inflammable
Explosive properties	Non-explosive
Oxidising properties	None
Specific gravity	N/A
pH value	Insoluble
Melting point (°C)	N/A

10. Stability & Reactivity

Chemical stability	The material is stable
Conditions/materials to avoid	None known
Hazardous decomposition products	None known
Hazardous polymerization products	None



11. Toxicological Information

Likely to be of low toxicity

12. Ecological Information

Ecotoxicity	Not known
Persistence	Not known

13. Disposal Considerations

Dispose in accordance with current waste Disposal regulations (for UK – Control of Pollution {Special Waste} Regulations 1980). Landfill is the most appropriate method.

14. Transport Information

UN/SI No.		Not classified
UN Class		Not classified
Packing group		Not classified
Road	UK	Not classified
	ADR	Not classified
Sea	IMO	Not classified
Air	ICAO	Not classified

15. Regulatory Information

EC Supply Labelling	Harmful Xn	
R Phrases	R20/22	Harmful by inhalation and if swallowed.
S Phrases	S22	Do not breathe dust.
	S25	Avoid contact with eyes.

UK Occupational exposures limits (Refer to HSE Guidance note EH40)	Mg/m ³	8 hr TWA	% in product
Antimony compounds	0.5	-	10
Chromium compounds	0.5		2

In accordance with HSE Approved Code of Practice for CHIP, the recipient is reminded of their obligations under both the Health and Safety at Work Act (HSWA) and the Control of Substances Hazardous to Health Regulations (COSHH), and that the information in any safety data sheet does not constitutes the user's assessment of workplace risk.



16. Other Information

References

COSHH ACOP	HSC approved Code of Practice for the Control of Substances Hazardous to Health Regulations 1994
CHIP 96	Chemicals (Hazard Information and Packaging for Supply) Regulations 1996
CHIP SDS ACOPS	HSC Approved Code of Practice for Safety Data Sheets in accordance with regulation 6 of the CHIP regulations.
HSE EH40	HSE Guidance note EH40 on Occupational Exposure Limits to be used in conjunction with the COSHH regulations.